

Product data sheet

Characteristics

E/SO110U

1 GANG SWITCHED UNIVERSAL SOCKET WITH USB



Main

Product Range	Esprit series
Product or component type	Socket-outlet
Height	86mm
Width	86mm
Projecting Depth	9mm

Color Units and Main Cover Materials

GW	GLASS , WHITE
GB	GLASS, BLACK
GC	GLASS, CHAMPAGNE

Complementary

Device mounting	Flush
Number of gangs	1 gang
Switch function	Single Pole
Pilot light	Neon Indicator lamp
Fixing mode	By screws M3.5
Fixing center	60.3mm
Embedding depth	35mm
Device presentation	Mechanism
Rated current	16A 220V AC 50/60Hz
Integrated connection type	5V 2.1A USB TYPE-A CHARGING PORT
Main Material	3mm Glass for Face-plate PC (Polycarbonate) for housing Steel for Back frame
Shape of screw head	Cross

Product data sheet

Characteristics

E/SO110U

1 GANG SWITCHED UNIVERSAL SOCKET WITH USB

Connections - terminals	Saddle terminal
Terminal identifier	N L E
Tightening torque	0.4 N.m
Wire stripping length	6 mm
Clamping connection capacity	3 x 2.5 mm ² - cable stiffness: solid 2 x 4 mm ² - cable stiffness: stranded

Environment

Standards	IEC 60884
Ambient air temperature for storage	-5...60 °C
Relative humidity	10...90 %
IP degree of protection	IP20
Environmental characteristic	Alcohol Liquid soap
Environmental health and issues	Halogen free